

# MANITOU MANISKOPISK MLT MLT 526 MONO-ULTRA SERIE 2



## MOTOR

Kapacitet: 7,6 liter

### ANVEND

Normal

### KLIMA

Moderat

#### PRODUKTANBEFALING 1

**Agridiesel CRD+ 15W-40**

#### PRODUKTANBEFALING 2

**Dieselfleet CD+ 15W-40**

#### PRODUKTANBEFALING 3

**Multifleet SHPD 15W-40**

*Skift alle 400 timer*

### ANVEND

Første Service

### KLIMA

Moderat

#### PRODUKTANBEFALING 1

**Agridiesel CRD+ 15W-40**

#### PRODUKTANBEFALING 2

**Dieselfleet CD+ 15W-40**

#### PRODUKTANBEFALING 3

**Multifleet SHPD 15W-40**

*Skift alle 50 timer*

## DIFFERENTIALE BAG

Kapacitet: 10 liter

### ANVEND

Normal

### KLIMA

Moderat

#### PRODUKTANBEFALING 1

**Agrifluid HT**

*Skift alle 800 timer*

## DIFFERENTIALE FOR

Kapacitet: 9,5 liter

### ANVEND

Normal

### KLIMA

Moderat

#### PRODUKTANBEFALING 1

**Agrifluid HT**

*Skift alle 800 timer*

## DREJELED TIL AKSEL BAG

### ANVEND

Normal

### KLIMA

Moderat

#### PRODUKTANBEFALING 1

**Q7 MP Calcep Grease WR 2**

#### PRODUKTANBEFALING 2

**Caliplex HD Grease EP 2**

#### PRODUKTANBEFALING 3

**Q5 MP Calcep Grease EP 2**

# MANITOU MANISKOPISK MLT MLT 526 MONO-ULTRA SERIE 2



## GEAR

Kapacitet: 8,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**ATF Almirol**

*Skift alle 800 timer*

## NAVREDUKTIONER BAG

Kapacitet: 0,8 liter (hvert nav)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Gearlube GL-5 80W-90**

PRODUKTANBEFALING 2

**Unigear HS GL-3/GL-5 80W-90**

*Skift alle 800 timer*

## NAVREDUKTIONER FOR

Kapacitet: 0,8 liter (hvert nav)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Gearlube GL-5 80W-90**

PRODUKTANBEFALING 2

**Unigear HS GL-3/GL-5 80W-90**

*Skift alle 800 timer*

## HYDRAULISK SYSTEM

Kapacitet: 110 liter (Hydrauliktank)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Perlus H 46**

*Skift alle 800 timer*

## HYDRAULISK BREMSESYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**LHM +**

# MANITOU MANISKOPISK MLT MLT 526 MONO-ULTRA SERIE 2



## SMØREPUNKTER/NIPLER

|                                             |                                                        |                                                     |
|---------------------------------------------|--------------------------------------------------------|-----------------------------------------------------|
| ANVEND<br>Normal                            |                                                        | KLIMA<br>Moderat                                    |
| PRODUKTANBEFALING 1<br><b>Labora Grease</b> | PRODUKTANBEFALING 2<br><b>Q5 MP Calcep Grease EP 2</b> | PRODUKTANBEFALING 3<br><b>MP Lithep Grease EP 2</b> |

## KØLESYSTEM

Kapacitet: 15 liter

|                                              |                                             |                                                      |
|----------------------------------------------|---------------------------------------------|------------------------------------------------------|
| ANVEND<br>Normal                             |                                             | KLIMA<br>Moderat                                     |
| PRODUKTANBEFALING 1<br><b>Coolant SP 15+</b> | PRODUKTANBEFALING 2<br><b>Coolant SP 12</b> | PRODUKTANBEFALING 3<br><b>Coolant -38 Organic NF</b> |

## GLIDEPUDER UDLIGGER

|                                                        |                                                       |                                                        |
|--------------------------------------------------------|-------------------------------------------------------|--------------------------------------------------------|
| ANVEND<br>Normal                                       |                                                       | KLIMA<br>Moderat                                       |
| PRODUKTANBEFALING 1<br><b>Q7 MP Calcep Grease WR 2</b> | PRODUKTANBEFALING 2<br><b>Caliplex HD Grease EP 2</b> | PRODUKTANBEFALING 3<br><b>Q5 MP Calcep Grease EP 2</b> |

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*