

MANITOU MANISKOPISK MLT MLT 735

TURBO LSU-SERIEN 5-E3



MOTOR

Kapacitet: 11 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2

Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 3

Multifleet SHPD 15W-40

Kontroller alle 8 timer, skift alle 6 måneder/ 500 timer

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2

Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 3

Multifleet SHPD 15W-40

Skift alle 50 timer

DIFFERENTIALE BAG

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT

Kontroller alle 250 timer, skift alle 6 måneder/ 500 timer

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT

Skift alle 50 timer

DIFFERENTIALE FOR

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT

Kontroller alle 250 timer, skift alle 6 måneder/ 500 timer

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT

Skift alle 50 timer

MANITOU MANISKOPISK MLT MLT 735 TURBO LSU-SERIEN 5-E3



DREJELED TIL AKSEL BAG

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
MoS2 Grease EP 2		
<i>Skift alle 50 timer</i>		

GEAR

Kapacitet: 16,6 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
ATF Almirol		
<i>Kontroller alle 8 timer, skift alle 12 måneder/ 1000 timer</i>		

ANVEND		KLIMA
Første Service		Moderat
PRODUKTANBEFALING 1		
ATF Almirol		
<i>Skift alle 50 timer</i>		

NAVREDUKTIONER BAG

Kapacitet: 0,75 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
<i>Kontroller alle 250 timer, skift alle 1000 timer/ 12 måneder</i>		

ANVEND		KLIMA
Første Service		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
<i>Skift alle 50 timer</i>		

MANITOU MANISKOPISK MLT MLT 735 TURBO LSU-SERIEN 5-E3



NAVREDUKTIONER FOR

Kapacitet: 0,75 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 250 timer, skift alle 1000 timer/ 12 måneder

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Skift alle 50 timer

VINKELGEARKASSE

Kapacitet: 2,2 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 250 timer, skift alle 1000 timer/ 12 måneder

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Skift alle 50 timer

HYDRAULISK SYSTEM

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Perlus H 46		

Kontroller alle 50 timer, skift alle 1000 timer/ 12 måneder

HYDRAULISK BREMSESYSTEM

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
LHM +		

Kontroller alle 50 timer, skift alle 1000 timer/ 12 måneder

MANITOU MANISKOPISK MLT MLT 735

TURBO LSU-SERIEN 5-E3



SMØREPUNKTER/NIPLER ANDRE

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Q7 MP Calcep Grease WR 2	Caliplex HD Grease EP 2	

SMØREPUNKTER/NIPLER BOOM-PUDER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
MoS2 Grease EP 2		
<i>Skift alle 10 timer</i>		

SMØREPUNKTER/NIPLER DREJETAP TIL HJULREDUKTIONSGEAR

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
MoS2 Grease EP 2		
<i>Skift alle 50 timer</i>		

SMØREPUNKTER/NIPLER TELESKOPISK ARM

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Q7 MP Calcep Grease WR 2	Caliplex HD Grease EP 2	
<i>Skift alle 50 timer</i>		

KØLESYSTEM

Kapacitet: 18,5 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Kontroller alle 8 timer, skift alle 24 måneder/ 2000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.