

MANITOU MANISKOPISK MLT MT 620

TURBO EVOLUTION-SERIE C-E3 KUBOTA

3307V-DI-T-E3B



MOTOR Kubota V3307-DI-TE3
Kapacitet: 11,2 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Kontroller alle 10 timer, skift alle 500 timer/ 12 måneder

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Skift alle 50 timer

DIFFERENTIALE BAG Dana
Kapacitet: 3,8 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Agrifluid HT		

Kontroller alle 250 timer, skift alle 500 timer/ 12 måneder

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1		
Agrifluid HT		

Skift alle 50 timer

DIFFERENTIALE FOR Dana
Kapacitet: 4 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Agrifluid HT		

Kontroller alle 250 timer, skift alle 500 timer/ 12 måneder

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1		
Agrifluid HT		

Skift alle 50 timer

MANITOU MANISKOPISK MLT MT 620 TURBO EVOLUTION-SERIE C-E3 KUBOTA 3307V-DI-T-E3B



NAVREDUKTIONER BAG

Kapacitet: 0,9 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 250 timer, skift alle 1000 timer/ 12 måneder

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Skift alle 50 timer

NAVREDUKTIONER FOR

Kapacitet: 0,9 liter (hvert nav)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 250 timer, skift alle 1000 timer/ 12 måneder

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Skift alle 50 timer

REDUKTIONSGEARKASSE

Kapacitet: 0,75 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 250 timer, skift alle 500 timer/ 12 måneder

MANITOU MANISKOPISK MLT MT 620

TURBO EVOLUTION-SERIE C-E3 KUBOTA

3307V-DI-T-E3B

**HYDRAULISK SYSTEM**

Kapacitet: 123 liter (Hydrauliktank)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 46*Kontroller alle 10 timer, skift alle 1000 timer/ 12 måneder***HYDRAULISK BREMSESYSTEM**

Kapacitet: 1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

LHM +*Kontroller alle 50 timer, skift alle 1000 timer/ 12 måneder***KØLESYSTEM**

Kapacitet: 13,7 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF*Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.