

MANITOU MANISKOPISK MT/MTA MT 222 CP



MOTOR Perkins 4.236
Kapacitet: 7,6 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	

Skift alle 150 timer

DIFFERENTIALE FOR Hurth
Kapacitet: 31,8 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Agrifluid HT		

Kontroller alle 150 timer, skift alle 900 timer/ 12 måneder

GEAR Borg Warner
Kapacitet: 8,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gear Oil Alcat 10W	ATF Dexron II-D	

Kontroller alle 150 timer, skift alle 900 timer/ 12 måneder

NAVREDUKTIONER FOR
Kapacitet: 1,1 liter (hvert nav)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 150 timer, skift alle 900 timer/ 12 måneder

HYDRAULISK SYSTEM
Kapacitet: 110 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Perlus H 46		

Kontroller alle 150 timer, skift alle 900 timer/ 12 måneder

MANITOU MANISKOPISK MT/MTA MT 222 CP



HYDRAULISK BREMSESYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

LHM +

SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

KØLESYSTEM

Kapacitet: 15 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

TELESKOPISK ARM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

MoS2 Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.