

MANITOU MANISKOPISK MT/MTA MT 430



MOTOR Perkins 4.236
Kapacitet: 12 liter

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1
Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 2
Multifleet SHPD 15W-40

DIFFERENTIALE + BREMSER I OLIE BAG Hurth
Kapacitet: 7,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 2
Agrifluid HT-Plus

PRODUKTANBEFALING 3
Kroontrak MTH 10W-30

DIFFERENTIALE FOR Hurth
Kapacitet: 8,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 2
Agrifluid HT-Plus

PRODUKTANBEFALING 3
Kroontrak MTH 10W-30

GEAR Clark 18000
Kapacitet: 18 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gear Oil Alcat 10W

PRODUKTANBEFALING 2
ATF Dexron II-D

NAVREDUKTIONER BAG
Kapacitet: 1 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 2
Agrifluid HT-Plus

PRODUKTANBEFALING 3
Kroontrak MTH 10W-30

MANITOU MANISKOPISK MT/MTA MT 430



NAVREDUKTIONER FOR

Kapacitet: 1 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30

HYDRAULISK SYSTEM

Kapacitet: 100 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Perlus H 46		

HYDRAULISK BREMSESYSTEM

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Perlus H 46		

SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

KØLESYSTEM

Kapacitet: 15,1 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

MANITOU MANISKOPISK MT/MTA MT 430



HYDRAULISK RYKKESYSTEM

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Drauliquid DOT 3		

TELESKOPISK ARM

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
MoS2 Grease EP 2		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.