

MANITOU MANISKOPISK MT/MTA MT 431 CP



MOTOR Perkins 4.236
Kapacitet: 7,6 liter

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1
Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 2
Multifleet SHPD 15W-40

Skift alle 150 timer

DIFFERENTIALE BAG
Kapacitet: 7 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube GL-5 80W-90

PRODUKTANBEFALING 2
Unigear HS GL-3/GL-5 80W-90

Skift alle 900 timer

DIFFERENTIALE FOR Hurth
Kapacitet: 8,3 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 2
Agrifluid HT-Plus

PRODUKTANBEFALING 3
Kroontrak MTH 10W-30

Skift alle 900 timer

GEAR Borg Warner
Kapacitet: 10 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gear Oil Alcat 10W

PRODUKTANBEFALING 2
ATF Dexron II-D

Skift alle 900 timer

NAVREDUKTIONER BAG
Kapacitet: 1 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube GL-5 80W-90

PRODUKTANBEFALING 2
Unigear HS GL-3/GL-5 80W-90

Skift alle 900 timer

MANITOU MANISKOPISK MT/MTA MT 431 CP



NAVREDUKTIONER FOR

Kapacitet: 1,1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Skift alle 900 timer

HYDRAULISK SYSTEM

Kapacitet: 73 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 46

Skift alle 900 timer

HYDRAULISK BREMSESYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

LHM +

SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

KØLESYSTEM

Kapacitet: 15 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

MANITOU MANISKOPISK MT/MTA MT 431 CP



TELESKOPISEK ARM		
ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Labora Grease	PRODUKTANBEFALING 2 Q5 MP Calcep Grease EP 2	PRODUKTANBEFALING 3 MP Lithep Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.