

# MANITOU MANISKOPISK MT/MTA MT 440 DCP



**MOTOR** Perkins 4.236  
Kapacitet: 12 liter

ANVEND  
Normal

KLIMA  
Middelhavsagtigt

PRODUKTANBEFALING 1  
**Dieselfleet CD+ 15W-40**

PRODUKTANBEFALING 2  
**Multifleet SHPD 15W-40**

*Skift alle 150 timer*

**DIFFERENTIALE BAG**  
Kapacitet: 5 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1  
**Gearlube GL-5 80W-90**

PRODUKTANBEFALING 2  
**Unigear HS GL-3/GL-5 80W-90**

*Skift alle 900 timer*

**DIFFERENTIALE FOR**  
Kapacitet: 5 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1  
**Gearlube GL-5 80W-90**

PRODUKTANBEFALING 2  
**Unigear HS GL-3/GL-5 80W-90**

*Skift alle 900 timer*

**GEAR** Clark 18000  
Kapacitet: 18 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1  
**Gear Oil Alcat 10W**

PRODUKTANBEFALING 2  
**ATF Dexron II-D**

PRODUKTANBEFALING 3  
**ATF-A**

*Skift alle 900 timer*

**NAVREDUKTIONER BAG**  
Kapacitet: 1 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1  
**Gearlube GL-5 80W-90**

PRODUKTANBEFALING 2  
**Unigear HS GL-3/GL-5 80W-90**

*Skift alle 900 timer*

# MANITOU MANISKOPISK MT/MTA MT 440 DCP



## NAVREDUKTIONER FOR

Kapacitet: 1 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |  |
|-----------------------------|------------------------------------|--|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

Skift alle 900 timer

## HYDRAULISK SYSTEM

Kapacitet: 140 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1 |  |  |
|---------------------|--|--|
| <b>Perlus H 46</b>  |  |  |

Skift alle 900 timer

## HYDRAULISK BREMSESYSTEM

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1              | PRODUKTANBEFALING 2       |  |
|----------------------------------|---------------------------|--|
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> |  |

## SMØREPUNKTER/NIPLER

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
|----------------------|---------------------------------|------------------------------|
| <b>Labora Grease</b> | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

## KØLESYSTEM

Kapacitet: 16 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1           | PRODUKTANBEFALING 2 |  |
|-------------------------------|---------------------|--|
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>  |  |

# MANITOU MANISKOPISK MT/MTA MT 440 DCP



## HYDRAULISK RYKKESYSTEM

| ANVEND                           |                           | KLIMA   |
|----------------------------------|---------------------------|---------|
| Normal                           |                           | Moderat |
| PRODUKTANBEFALING 1              | PRODUKTANBEFALING 2       |         |
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> |         |

## TELESKOPISK ARM

| ANVEND                  |  | KLIMA   |
|-------------------------|--|---------|
| Normal                  |  | Moderat |
| PRODUKTANBEFALING 1     |  |         |
| <b>MoS2 Grease EP 2</b> |  |         |

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*