

# MANITOU MANISKOPISK MT/MTA MT 8044XT JOHN DEERE 4045T TIER 3 (18201- >)



**MOTOR** John Deere 4045 T  
Kapacitet: 14,7 liter

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

**Agrisynth LSP Ultra 10W-40**

PRODUKTANBEFALING 2

**Agrisynth LSP 10W-40**

PRODUKTANBEFALING 3

**AgriDiesel CRD+ 15W-40**

*Skift alle 100 timer*

ANVEND

Normalt, svovlniveau i brændstof <0,1 %

KLIMA

Moderat

PRODUKTANBEFALING 1

**Agrisynth LSP Ultra 10W-40**

PRODUKTANBEFALING 2

**Agrisynth LSP 10W-40**

PRODUKTANBEFALING 3

**AgriDiesel CRD+ 15W-40**

*Kontroller alle 10 timer, skift alle 250 timer/ 3 måneder*

**DIFFERENTIALE BAG** Dana  
Kapacitet: 15 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Agrifluid HT-Plus**

*Kontroller alle 250 timer, skift alle 1000 timer/ 12 måneder*

**DIFFERENTIALE FOR** Dana  
Kapacitet: 15 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Agrifluid HT-Plus**

*Kontroller alle 250 timer, skift alle 1000 timer/ 12 måneder*

# MANITOU MANISKOPISK MT/MTA MT 8044XT JOHN DEERE 4045T TIER 3 (18201- >)



**GEAR POWERSHIFT** Clark T12000 3/3  
Kapacitet: 22,7 liter (+ køler)

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2 |  |
|----------------------|---------------------|--|
| <b>SP Matic 2032</b> | <b>ATF Almirol</b>  |  |

Kontroller alle 10 timer, skift alle 1000 timer/ 12 måneder

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Moderat |

| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2 |  |
|----------------------|---------------------|--|
| <b>SP Matic 2032</b> | <b>ATF Almirol</b>  |  |

Skift alle 100 timer

**NAVREDUKTIONER BAG**  
Kapacitet: 2,5 liter (hvert nav)

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1      |  |  |
|--------------------------|--|--|
| <b>Agrifluid HT-Plus</b> |  |  |

Kontroller alle 250 timer, skift alle 1000 timer/ 12 måneder

**NAVREDUKTIONER FOR**  
Kapacitet: 2,5 liter (hvert nav)

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1      |  |  |
|--------------------------|--|--|
| <b>Agrifluid HT-Plus</b> |  |  |

Kontroller alle 250 timer, skift alle 1000 timer/ 12 måneder

**HYDRAULISK SYSTEM**

Kapacitet: 170 liter (Hydrauliksystem inkl. tank), Kapacitet: 113,5 liter (Hydrauliktank)

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1 |  |  |
|---------------------|--|--|
| <b>Perlus H 46</b>  |  |  |

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

# MANITOU MANISKOPISK MT/MTA MT 8044XT JOHN DEERE 4045T TIER 3 (18201- >)



## HYDRAULISK BREMSESYSTEM

| ANVEND               |                     | KLIMA   |
|----------------------|---------------------|---------|
| Normal               |                     | Moderat |
| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2 |         |
| <b>SP Matic 2032</b> | <b>ATF Almirol</b>  |         |

Kontroller alle 10 timer, skift alle 1000 timer/ 12 måneder

## SMØREPUNKTER/NIPLER

| ANVEND               |                                 | KLIMA                        |
|----------------------|---------------------------------|------------------------------|
| Normal               |                                 | Moderat                      |
| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
| <b>Labora Grease</b> | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

## KØLESYSTEM

Kapacitet: 16,3 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*