

MANITOU MANISKOPISK MT/MTA MT 835 ST3B PERKINS 854E-E34TA STAGE IIIB (2014 OG EFTER)



MOTOR Perkins 854E-E34TA
Kapacitet: 7,5 liter

ANVEND	KLIMA
Første Service	Middelhavsagtigt

PRODUKTANBEFALING 1		
Dieselfleet MSP 15W-40		

Skift alle 50 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP Ultra FE 5W-30	Agrisynth LSP Ultra 10W-40	Agrisynth MSP 10W-40

Skift alle 50 timer

ANVEND	KLIMA
Normalt, svovlniveau i brændstof < 0,001 %	Middelhavsagtigt

PRODUKTANBEFALING 1		
Dieselfleet MSP 15W-40		

Kontroller alle 8 timer, skift alle 500 timer

ANVEND	KLIMA
Normalt, svovlniveau i brændstof < 0,001 %	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP Ultra FE 5W-30	Agrisynth LSP Ultra 10W-40	Agrisynth MSP 10W-40

Kontroller alle 8 timer, skift alle 500 timer

DIFFERENTIALE BAG Dana
Kapacitet: 7,2 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Agrifluid HT		

Kontroller alle 250 timer, skift alle 500 timer/ 12 måneder

DIFFERENTIALE FOR Dana
Kapacitet: 7,2 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Agrifluid HT		

Kontroller alle 250 timer, skift alle 500 timer/ 12 måneder

MANITOU MANISKOPISK MT/MTA MT 835 ST3B PERKINS 854E-E34TA STAGE IIIB (2014 OG EFTER)



GEAR POWERSHIFT Dana 4/4
Kapacitet: 21,1 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
ATF Almirol		

Kontroller alle 50 timer, skift alle 1000 timer/ 24 måneder

NAVREDUKTIONER BAG
Kapacitet: 0,75 liter (hvert)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 250 timer, skift alle 1000 timer/ 24 måneder

NAVREDUKTIONER FOR
Kapacitet: 0,75 liter (hvert)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 250 timer, skift alle 1000 timer/ 24 måneder

HYDRAULISK SYSTEM
Kapacitet: 175 liter (Hydrauliktank)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Perlus H 46		

Kontroller alle 50 timer, skift alle 1000 timer/ 24 måneder

HYDRAULISK BREMSESYSTEM
Kapacitet: 0,75 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
LHM +		

Kontroller alle 50 timer, skift alle 2000 timer/ 24 måneder

MANITOU MANISKOPISK MT/MTA MT 835 ST3B PERKINS 854E-E34TA STAGE IIIB (2014 OG EFTER)



KØLESYSTEM

Kapacitet: 17 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.