

MANITOU MANISCOPIC MT/MTA MT 927



ENGINE

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	

Change every 300 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	

Change every 50 hours

AXLE ARTICULATIONS WITH WIELAND BUSHINGS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

DIFFERENTIAL FRONT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		

Change every 900 hours

DIFFERENTIAL REAR

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 900 hours

MANITOU MANISCOPIC MT/MTA MT 927



HUB REDUCTIONS FRONT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 900 hours

HUB REDUCTIONS REAR

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 900 hours

TRANSFERBOX

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 900 hours

TRANSMISSION

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 10W	ATF Dexron II-D	

Change every 900 hours

HYDRAULIC SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 46		

Change every 900 hours

MANITOU MANISCOPIC MT/MTA MT 927



HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
LHM +		

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

TELESCOPIC JIB PADS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.