

# MANITOU MANITRANSIT UDVALG

## TMD/TME/TMP/TMT/TMV TMV 50 PERKINS

### 404C--22 TIER 2 (755748 ->)



**MOTOR** Perkins 404C-22  
Kapacitet: 5,6 liter

| ANVEND | KLIMA            |
|--------|------------------|
| Normal | Middelhavsagtigt |

| PRODUKTANBEFALING 1          | PRODUKTANBEFALING 2           | PRODUKTANBEFALING 3           |
|------------------------------|-------------------------------|-------------------------------|
| <b>Agridiesel MSP 15W-40</b> | <b>Agridiesel CRD+ 15W-40</b> | <b>Dieselfleet CD+ 15W-40</b> |

Kontroller alle 10 timer, skift alle 200 timer

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2       | PRODUKTANBEFALING 3                 |
|-----------------------------|---------------------------|-------------------------------------|
| <b>Synfleet SHPD 10W-40</b> | <b>Armado Synth 5W-30</b> | <b>Dieselfleet LSP Ultra 10W-30</b> |

Kontroller alle 10 timer, skift alle 200 timer

| ANVEND         | KLIMA            |
|----------------|------------------|
| Første Service | Middelhavsagtigt |

| PRODUKTANBEFALING 1          | PRODUKTANBEFALING 2           | PRODUKTANBEFALING 3           |
|------------------------------|-------------------------------|-------------------------------|
| <b>Agridiesel MSP 15W-40</b> | <b>Agridiesel CRD+ 15W-40</b> | <b>Dieselfleet CD+ 15W-40</b> |

Skift alle 50 timer

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Moderat |

| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2       | PRODUKTANBEFALING 3                 |
|-----------------------------|---------------------------|-------------------------------------|
| <b>Synfleet SHPD 10W-40</b> | <b>Armado Synth 5W-30</b> | <b>Dieselfleet LSP Ultra 10W-30</b> |

Skift alle 50 timer

**HYDRAULISK SYSTEM**  
Kapacitet: 40 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1 |  |  |
|---------------------|--|--|
| <b>Perlus H 46</b>  |  |  |

Kontroller alle 50 timer, skift alle 800 timer/ 12 måneder

#### SMØREPUNKTER/NIPLER GENERELT

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1     |  |  |
|-------------------------|--|--|
| <b>MoS2 Grease EP 2</b> |  |  |

# MANITOU MANITRANSIT UDVALG TMD/TME/TMP/TMT/TMV TMV 50 PERKINS 404C--22 TIER 2 (755748 ->)



## SMØREPUNKTER/NIPLER MASTHOLDER TRYKPUDER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**MoS2 Grease EP 2**

*Skift alle 10 timer*

## KØLESYSTEM

Kapacitet: 8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Coolant -38 Organic NF**

*Kontroller alle 10 timer, skift alle 800 timer/ 12 måneder*

## TELESKOPARMKÆDER

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*