

MANITOU MC MC 30 SERIER 3-E2



MOTOR

Kapacitet: 8,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2

Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 3

Multifleet SHPD 15W-40

DIFFERENTIALE FOR

Kapacitet: 6,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT

DREJELED TIL AKSEL BAG

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

GEAR

Kapacitet: 15,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Almirol

NAVREDUKTIONER FOR

Kapacitet: 0,75 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

MANITOU MC MC 30 SERIER 3-E2



HYDRAULISK SYSTEM

Kapacitet: 64 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 46

HYDRAULISK BREMSESYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

LHM +

SMØREPUNKTER/NIPLER ANDRE

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

SMØREPUNKTER/NIPLER TELESKOPARM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Q7 MP Calcep Grease WR 2

PRODUKTANBEFALING 2

Caliplex HD Grease EP 2

PRODUKTANBEFALING 3

Q5 MP Calcep Grease EP 2

KØLESYSTEM

Kapacitet: 13 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.