

MANITOU MINI-ACCESS AE (AEXXX)/ATXX/TM 120 AETJL (2007-2011)



BAGHJUL REDUKTIONSHJUL

Kapacitet: 0,8 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Skift alle 1000 timer

HYDRAULISK SYSTEM

Kapacitet: 12 liter (Hydrauliktank)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Perlus H 46		

Skift alle 1000 timer/ 12 måneder

SMØREPUNKTER/NIPLER

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
MoS2 Grease EP 2		

SMØREPUNKTER/NIPLER RETNINGSRINGGEAR

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
MoS2 Grease EP 2		

SMØREPUNKTER/NIPLER RINGGEAR

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Compound OGL		

MANITOU MINI-ACCESS AE (AEXXX)/ATXX/TM 120 AETJL (2007-2011)



TÅRN DREJEMOTOR

Kapacitet: 1,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.