

MANITOU TELESKOPISE ARBEJDSPLATFORME 170 ATT PERKINS 903-27 (1998-2001)



MOTOR Perkins 903-27
Kapacitet: 5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2
Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 3
Multifleet SHPD 15W-40

DIFFERENTIALE BAG
Kapacitet: 9,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agrifluid HT

DIFFERENTIALE FOR
Kapacitet: 10 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agrifluid HT

NAVREDUKTIONER BAG
Kapacitet: 0,8 liter (hvert nav)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube GL-5 80W-90

PRODUKTANBEFALING 2
Unigear HS GL-3/GL-5 80W-90

NAVREDUKTIONER FOR
Kapacitet: 0,8 liter (hvert nav)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube GL-5 80W-90

PRODUKTANBEFALING 2
Unigear HS GL-3/GL-5 80W-90

MANITOU TELESKOPISE ARBEJDSPLATFORME 170 ATT PERKINS 903-27 (1998-2001)

**REDUKTIONSGEARKASSE**

Kapacitet: 0,6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90**HYDRAULISK SYSTEM**

Kapacitet: 75 liter (Hydrauliktank)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 46**SMØREPUNKTER/NIPLER**

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Q7 MP Calcep Grease WR 2

PRODUKTANBEFALING 2

Caliplex HD Grease EP 2**KØLESYSTEM**

Kapacitet: 10 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF**TÅRNETS TÆNDER RINGGEAR**

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Compound OGL

PRODUKTANBEFALING 2

Compound OGL EP 0/1

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.