

MECALAC GRAVEMASKINER MED HJUL 12 MTX STAGE IIIB (2009-2014)



MOTOR Cummins 4BT4.5C
Kapacitet: 11 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40

Kontroller alle 8 timer, skift alle 250 timer

DIFFERENTIALE BAG
Kapacitet: 6,7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

Kontroller alle 250 timer, skift alle 1000 timer

ANVEND	KLIMA
Første skift kun	Moderat

PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

Skift alle 100 timer

DIFFERENTIALE FOR
Kapacitet: 6,8 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

Kontroller alle 250 timer, skift alle 1000 timer

ANVEND	KLIMA
Første skift kun	Moderat

PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

Skift alle 100 timer

MECALAC GRAVEMASKINER MED HJUL 12 MTX STAGE IIIB (2009-2014)



NAVREDUKTIONER

Kapacitet: 0,75 liter (hvert nav)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Kontroller alle 250 timer, skift alle 1000 timer

ANVEND

Første skift kun

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Skift alle 100 timer

REDUKTIONSGEARKASSE

Kapacitet: 1,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Kontroller alle 250 timer, skift alle 1000 timer

ANVEND

Første skift kun

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Skift alle 100 timer

HYDRAULISK SYSTEM

Kapacitet: 82 liter (Tank), Kapacitet: 135 liter (Total)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus Biosynth 46

PRODUKTANBEFALING 2

Perlus H 46

Kontroller alle 8 timer, skift alle 1500 timer/ 12 måneder

MECALAC GRAVEMASKINER MED HJUL 12 MTX STAGE IIIB (2009-2014)



SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

Kontroller alle 8 timer, skift alle 100 timer/ 12 måneder

KØLESYSTEM

Kapacitet: 14 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

Kontroller alle 8 timer, skift alle 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.