

MECALAC GUMMIHJULSLÆSSERE AF/AS/AZ AF 1200 CUMMINS B3.3T (2010 OG EFTER)



MOTOR Cummins B3.3T
Kapacitet: 8 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Dieselfleet MSP 15W-40

Kontroller alle 10 timer, skift alle 250 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Dieselfleet MSP 15W-40

Kontroller alle 10 timer, skift alle 50 timer

DIFFERENTIALE BAG
Kapacitet: 5,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

Kontroller alle 50 timer, skift alle 1500 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

Kontroller alle 50 timer, skift alle 500 timer

NAVREDUKTIONER BAG
Kapacitet: 0,8 liter (hver side)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

Kontroller alle 50 timer, skift alle 1500 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

Kontroller alle 50 timer, skift alle 500 timer

MECALAC GUMMIHJULSLÆSSERE AF/AS/AZ AF 1200 CUMMINS B3.3T (2010 OG EFTER)



NAVREDUKTIONER FOR

Kapacitet: 0,8 liter (hver side)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Kontroller alle 50 timer, skift alle 1500 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Kontroller alle 50 timer, skift alle 500 timer

REDUKTIONSGEARKASSE

Kapacitet: 1,25 liter (20 km/t version), Kapacitet: 4 liter (30 km/t version)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Kontroller alle 50 timer, skift alle 1500 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Kontroller alle 50 timer, skift alle 500 timer

SELVSPÆRRENDE DIFFERENTIALE FOR

Kapacitet: 5,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Kontroller alle 50 timer, skift alle 1500 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Kontroller alle 50 timer, skift alle 500 timer

MECALAC GUMMIHJULSLÆSSERE AF/AS/AZ AF 1200 CUMMINS B3.3T (2010 OG EFTER)

**HYDRAULISK SYSTEM**

Kapacitet: 80 liter (Hydrauliktank), Kapacitet: 134 liter (Total)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 46*Kontroller alle 10 timer, skift alle 1500 timer***SMØREPUNKTER/NIPLER**

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

MoS2 Grease EP 2*Kontroller alle 10 timer***KØLESYSTEM**

Kapacitet: 14 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF*Kontroller alle 50 timer, skift alle 1500 timer*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.