

MERLO SPOREDE MASKINER TIL SKOVBRUG P40.14 K DEUTZ TCD 2012 L04 2V (2003-2006)



MOTOR Deutz TCD 2012 L04 2V
Kapacitet: 8,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak CVT 10W-40	Agridiesel CRD+ 15W-40	Kroontrak MTH 10W-30

Skift alle 400 timer/ 6 måneder

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak CVT 10W-40	Agridiesel CRD+ 15W-40	Kroontrak MTH 10W-30

Skift alle 100 timer

DIFFERENTIALE
Kapacitet: 5,3 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Skift alle 400 timer/ 6 måneder

GEAR HYDROSTATISK Rexroth
Kapacitet: 12 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Perlus H 46		

Skift alle 1600 timer/ 12 måneder

GEARKASSE
Kapacitet: 4 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Skift alle 400 timer/ 6 måneder

MERLO SPOREDE MASKINER TIL SKOVBRUG P40.14 K DEUTZ TCD 2012 L04 2V (2003-2006)

**NAVREDUKTIONER**

Kapacitet: 1,3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90*Skift alle 400 timer/ 6 måneder***HYDRAULISK SYSTEM**

Kapacitet: 95 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 46*Skift alle 1600 timer/ 12 måneder***HYDRAULISK BREMSESYSTEM**

Kapacitet: 0,3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4**KØLESYSTEM**

Kapacitet: 12 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.