

MITSUBISHI GAFFELTRUCK, DIESEL FD50



MOTOR Mitsubishi
Kapacitet: 11,8 liter

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1

HDX 30

Kontroller alle 10 timer, skift alle 200 timer

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Kroontrak MTH 10W-30

Kontroller alle 10 timer, skift alle 200 timer

ANVEND
Normal

KLIMA
Koldt

PRODUKTANBEFALING 1

HDX 20W-20

Kontroller alle 10 timer, skift alle 200 timer

ANVEND
Normal

KLIMA
Arktisk

PRODUKTANBEFALING 1

HDX 10W

Kontroller alle 10 timer, skift alle 200 timer

DIFFERENTIALE
Kapacitet: 9,1 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Skift alle 6 måneder/ 1200 timer

GEAR Powershift
Kapacitet: 14 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Skift alle 6 måneder/ 1200 timer

MITSUBISHI GAFFELTRUCK, DIESEL FD50



HYDRAULISK SYSTEM POWERSHIFT-TRANSMISSION

Kapacitet: 67 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1

Perlus H 32

Skift alle 12 måneder/ 2400 timer

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1

Perlus H 22

Skift alle 12 måneder/ 2400 timer

HYDRAULISK BREMSESYSTEM

Kapacitet: 0,18 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Skift alle 12 måneder/ 2400 timer

FEDTSMURTE STEDER/NIPLER CHASSIS

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Gear Grease EP 1

SMØREPUNKTER/NIPLER GLIDENDE OVERFLADER PÅ TELESKOPARM

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

MoS2 Grease EP 2

MITSUBISHI GAFFELTRUCK, DIESEL FD50



KØLESYSTEM

Kapacitet: 11 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

HJULLEJER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

STYRINGSGEARKASSE

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.