

MITSUBISHI GAFFELTRUCK, DIESEL FD90



MOTOR

Kapacitet: 13,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

HDX 30

PRODUKTANBEFALING 2

HDX 10W

Kontroller alle 10 timer, skift alle 200 timer

ANVEND

Normal

KLIMA

Koldt

PRODUKTANBEFALING 1

HDX 20W-20

Kontroller alle 10 timer, skift alle 200 timer

DIFFERENTIALE FOR

Kapacitet: 20 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Skift alle 6 måneder/ 1200 timer

ANVEND

Normal

KLIMA

Arktisk

PRODUKTANBEFALING 1

Agrifluid HT-Plus

PRODUKTANBEFALING 2

SP Gear 5015

PRODUKTANBEFALING 3

Gearlube GL-4 80W

Skift alle 6 måneder/ 1200 timer

GEAR Powershift

Kapacitet: 22 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF-A

Skift alle 6 måneder/ 1200 timer

MITSUBISHI GAFFELTRUCK, DIESEL FD90



HYDRAULISK SYSTEM

Kapacitet: 143 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Perlus H 32

Skift alle 12 måneder/ 2400 timer

ANVEND

Normal

KLIMA

Arktisk

PRODUKTANBEFALING 1

Perlus H 22

Skift alle 12 måneder/ 2400 timer

HYDRAULISK BREMSESYSTEM

Kapacitet: 0,51 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Skift alle 12 måneder/ 2400 timer

FEDTSMURTE STEDER/NIPLER CHASSIS

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gear Grease EP 1

KØLESYSTEM

Kapacitet: 23 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

MITSUBISHI GAFFELTRUCK, DIESEL FD90



HJULLEJER		
ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Labora Grease	PRODUKTANBEFALING 2 Q5 MP Calcep Grease EP 2	PRODUKTANBEFALING 3 MP Lithep Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.