

MITSUBISHI GAFFELTRUCKS, LP- GAS/BENZIN FGC70K AF89-00001->



MOTOR

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1		
HDX 30		

Skift alle 200 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Kroontrak MTH 10W-30	HDX 10W	

Skift alle 200 timer

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1		
HDX 20W-20		

Skift alle 200 timer

DIFFERENTIALE FOR

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	

Skift alle 6 måneder/ 1200 timer

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid HT-Plus	SP Gear 5015	Gearlube GL-4 80W

Skift alle 6 måneder/ 1200 timer

GEAR Powershift

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
ATF-A		

Skift alle 6 måneder/ 1200 timer

MITSUBISHI GAFFELTRUCKS, LP- GAS/BENZIN FGC70K AF89-00001->



HYDRAULISK SYSTEM

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1
HDX 10W

Skift alle 12 måneder/ 2400 timer

HYDRAULISK BREMSESYSTEM

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2
Drauliquid-S DOT 4

Skift alle 12 måneder/ 2400 timer

FEDTSMURTE STEDER/NIPLER CHASSIS

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gear Grease EP 1

KØLESYSTEM

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Coolant -38 Organic NF

PRODUKTANBEFALING 2
Coolant -26

HJULLEJER

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Labora Grease

PRODUKTANBEFALING 2
Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3
MP Lithep Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.