

MITSUBISHI GAFFELTRUCKS, LPG FG18N EF34L-40001->



MOTOR

Kapacitet: 3,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Synfleet SHPD 10W-40

PRODUKTANBEFALING 2

Dieselfleet MSP 10W-30

Skift alle 500 timer/ 3 måneder

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Synfleet SHPD 10W-40

PRODUKTANBEFALING 2

Dieselfleet MSP 10W-30

Skift alle 1 måneder

DIFFERENTIALE

Kapacitet: 5 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

PRODUKTANBEFALING 2

Gearlube GL-5 80W-90

PRODUKTANBEFALING 3

Unigear HS GL-3/GL-5 80W-90

Skift alle 6 måneder/ 1200 timer

ANVEND

Normal

KLIMA

Arktisk

PRODUKTANBEFALING 1

Agrifluid HT-Plus

PRODUKTANBEFALING 2

SP Gear 5015

PRODUKTANBEFALING 3

SP Gear 1071

Skift alle 6 måneder/ 1200 timer

GEAR Powershift

Kapacitet: 8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Skift alle 6 måneder/ 1200 timer

MITSUBISHI GAFFELTRUCKS, LPG FG18N EF34L-40001->



REDUKTIONSGEARKASSE

Kapacitet: 5 liter

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Gearlube GL-4 80W-90	Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Skift alle 6 måneder/ 1200 timer

ANVEND		KLIMA
Normal		Arktisk
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid HT-Plus	SP Gear 5015	SP Gear 1071

Skift alle 6 måneder/ 1200 timer

HYDRAULISK SYSTEM

Kapacitet: 28 liter (Hydrauliktank)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Perlus H 32		

Skift alle 12 måneder/ 2400 timer

HYDRAULISK BREMSESYSTEM

Kapacitet: 0,14 liter (Tank)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Skift alle 12 måneder/ 2400 timer

FEDTSMURTE STEDER/NIPLER CHASSIS

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Gear Grease EP 1		

MITSUBISHI GAFFELTRUCKS, LPG FG18N EF34L-40001->



KØLESYSTEM

Kapacitet: 7,4 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26*Skift alle 12 måneder/ 2400 timer*

HJULLEJER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.