

# NEW HOLLAND GRAVEMASKINER MED HJUL MH/WE MH PLUS CNH 667TA/BEC TIER 3A (2008-2012)



**MOTOR** CNH 667TA/BEC  
Kapacitet: 13,2 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1  
**Agridiesel MSP 15W-40**

PRODUKTANBEFALING 2  
**Agridiesel CRD+ 15W-40**

PRODUKTANBEFALING 3  
**Dieselfleet CD+ 15W-40**

*Skift alle 500 timer*

ANVEND  
Første Service

KLIMA  
Moderat

PRODUKTANBEFALING 1  
**Agridiesel MSP 15W-40**

PRODUKTANBEFALING 2  
**Agridiesel CRD+ 15W-40**

PRODUKTANBEFALING 3  
**Dieselfleet CD+ 15W-40**

*Skift alle 250 timer*

**DIFFERENTIALE FAST AKSEL**  
Kapacitet: 2,4 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

**DIFFERENTIALE STYRET AKSEL**  
Kapacitet: 11 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

**FAST AKSEL**  
Kapacitet: 7,8 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

**NAVREDUKTIONER FAST AKSEL**  
Kapacitet: 2 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

**NAVREDUKTIONER STYRET AKSEL**  
Kapacitet: 2,5 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

**HYDRAULISK SYSTEM**  
Kapacitet: 170 liter (Tank), Kapacitet: 250 liter (Total)

ANVEND  
Normal

KLIMA  
Middelhavsagtigt

PRODUKTANBEFALING 1  
**Perlus H 68**

*Skift alle 36 måneder/ 3000 timer*

# NEW HOLLAND GRAVEMASKINER MED HJUL MH/WE MH PLUS CNH 667TA/BEC TIER 3A (2008-2012)



## DREJERINGGEARING

| ANVEND                  |  | KLIMA   |
|-------------------------|--|---------|
| Normal                  |  | Moderat |
| PRODUKTANBEFALING 1     |  |         |
| <b>MoS2 Grease EP 2</b> |  |         |

## KØLESYSTEM

Kapacitet: 25 liter

| ANVEND                |                      | KLIMA   |
|-----------------------|----------------------|---------|
| Normal                |                      | Moderat |
| PRODUKTANBEFALING 1   | PRODUKTANBEFALING 2  |         |
| <b>Coolant SP 15+</b> | <b>Coolant SP 12</b> |         |

Skift alle 2000 timer

## SVINGREDUKTIONSENHED

Kapacitet: 5,5 liter

| ANVEND                      |                                    | KLIMA   |
|-----------------------------|------------------------------------|---------|
| Normal                      |                                    | Moderat |
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |         |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |         |

Skift alle 36 måneder/ 3000 timer

| ANVEND                      |                                    | KLIMA   |
|-----------------------------|------------------------------------|---------|
| Første Service              |                                    | Moderat |
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |         |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |         |

Skift alle 250 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.