

NEW HOLLAND GRAVEMASKINER MED HJUL MH/WE WE170B CNH F4GE9684D*J602 EU STAGE 3A (2010-2015)



MOTOR CNH F4GE9684D
Kapacitet: 15 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40

DIFFERENTIALE BAG
Kapacitet: 12 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Unigear LS GL-3/GL-5 85W-140		

DIFFERENTIALE FOR
Kapacitet: 9,5 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Unigear LS GL-3/GL-5 85W-140		

GEAR POWERSHIFT
Kapacitet: 2,5 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40

NAVREDUKTIONER BAG
Kapacitet: 2,5 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Unigear LS GL-3/GL-5 85W-140		

NEW HOLLAND GRAVEMASKINER MED HJUL MH/WE WE170B CNH F4GE9684D*J602 EU STAGE 3A (2010-2015)



NAVREDUKTIONER FOR

Kapacitet: 2,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Unigear LS GL-3/GL-5 85W-140

HYDRAULISK SYSTEM

Kapacitet: 215 liter (System inkl. tank (enkelt led)), Kapacitet: 230 liter (System inkl. tank (tredobbelt led)), Kapacitet: 160 liter (Tank)

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Perlus H 68

KØLESYSTEM

Kapacitet: 11 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.