

# NEW HOLLAND GRAVEMASKINER MED LARVEBÅND E E245 CNH F4BE0684B\*D402 TIER 2 (2005-2007)



**MOTOR** CNH F4BE0684B  
Kapacitet: 16,9 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1          | PRODUKTANBEFALING 2           | PRODUKTANBEFALING 3           |
|------------------------------|-------------------------------|-------------------------------|
| <b>Agridiesel MSP 15W-40</b> | <b>Agridiesel CRD+ 15W-40</b> | <b>Dieselfleet CD+ 15W-40</b> |

Skift alle 500 timer

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Moderat |

| PRODUKTANBEFALING 1          | PRODUKTANBEFALING 2           | PRODUKTANBEFALING 3           |
|------------------------------|-------------------------------|-------------------------------|
| <b>Agridiesel MSP 15W-40</b> | <b>Agridiesel CRD+ 15W-40</b> | <b>Dieselfleet CD+ 15W-40</b> |

Skift alle 50 timer

**KØREREDUKTIONSENHEDER**  
Kapacitet: 3,5 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |  |
|-----------------------------|------------------------------------|--|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

Skift alle 2000 timer

**HYDRAULISK SYSTEM**  
Kapacitet: 270 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1       | PRODUKTANBEFALING 2 |  |
|---------------------------|---------------------|--|
| <b>Perlus Biosynth 46</b> | <b>Perlus H 46</b>  |  |

Skift alle 2500 timer

**SMØREPUNKTER/NIPLER**

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1     |  |  |
|-------------------------|--|--|
| <b>MoS2 Grease EP 2</b> |  |  |

# NEW HOLLAND GRAVEMASKINER MED LARVEBÅND E E245 CNH F4BE0684B\*D402 TIER 2 (2005-2007)



## KØLESYSTEM

Kapacitet: 24 liter

### ANVEND

Normal

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Coolant SP 15+**

### PRODUKTANBEFALING 2

**Coolant SP 12**

*Skift alle 2000 timer*

## DREJEGEAR

### ANVEND

Normal

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**MoS2 Grease EP 2**

## SVINGREDUKTIONSENHED

Kapacitet: 7,5 liter

### ANVEND

Normal

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Gearlube GL-5 80W-90**

### PRODUKTANBEFALING 2

**Unigear HS GL-3/GL-5 80W-90**

*Skift alle 1000 timer*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.