

NEW HOLLAND GRAVEMASKINER MED LARVEBÅND E E265C LC FPT F4HFE613R- A0004 STAGE 3B/TIER 4I (2011-2015)



MOTOR FPT F4HFE613R
Kapacitet: 18,3 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40

KØREREDUKTIONSENHEDER
Kapacitet: 5 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

HYDRAULISK SYSTEM

Kapacitet: 172 liter (Tank), Kapacitet: 280 liter (Total)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 46	Perlus AF 46	

SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Q7 MP Calcep Grease WR 2	Caliplex HD Grease EP 2	Q5 MP Calcep Grease EP 2

KØLESYSTEM

Kapacitet: 25 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant SP 15+	Coolant SP 12	

NEW HOLLAND GRAVEMASKINER MED LARVEBÅND E E265C LC FPT F4HFE613R- A0004 STAGE 3B/TIER 4I (2011-2015)



DREJEGEAR

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
MoS2 Grease EP 2		

SVINGREDUKTIONSENHED

Kapacitet: 12 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.