

NEW HOLLAND GRAVEMASKINER MED LARVEBÅND E E305 EVOLUTION CNH F4AE0684L*D101 TIER 2 (2005-2007)



MOTOR CNH F4AE0684L
Kapacitet: 17 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40

Skift alle 500 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40

Skift alle 50 timer

KØREREDUKTIONSENHEDER
Kapacitet: 7,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Skift alle 2000 timer

HYDRAULISK SYSTEM
Kapacitet: 280 liter (System), Kapacitet: 180 liter (Tank)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus Biosynth 46	Perlus H 46	

Skift alle 2500 timer

SMØREPUNKTER/NIPLER

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Q7 MP Calcep Grease WR 2	Caliplex HD Grease EP 2	Q5 MP Calcep Grease EP 2

NEW HOLLAND GRAVEMASKINER MED LARVEBÅND E E305 EVOLUTION CNH F4AE0684L*D101 TIER 2 (2005-2007)



KØLESYSTEM

Kapacitet: 23 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

Skift alle 2000 timer

DREJEGEAR

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

MoS2 Grease EP 2

SVINGREDUKTIONSENHED

Kapacitet: 10,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Skift alle 1000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.