

NEW HOLLAND GUMMIHJULSLÆSSERE LW/W W170B JSS FPT 667TA/EB3 TIER III (2007-2012)



MOTOR FPT 667TA/EB3

Kapacitet: 13,2 liter, Filterkapacitet: 0,9 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40

DIFFERENTIALE BAG

Kapacitet: 27,4 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Unigear LS GL-3/GL-5 85W-140		

DIFFERENTIALE FOR

Kapacitet: 30,3 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Unigear LS GL-3/GL-5 85W-140		

GEAR POWERSHIFT 4/3

Kapacitet: 25,6 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30	

HYDRAULISK SYSTEM

Kapacitet: 105,7 liter (Tank), Kapacitet: 177,8 liter (Total)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus Biosynth 46	Perlus H 46	

NEW HOLLAND GUMMIHJULSLÆSSERE LW/W W170B JSS FPT 667TA/EB3 TIER III (2007-2012)



SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

MoS2 Grease EP 2

KØLESYSTEM

Kapacitet: 28,4 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.