

NEW HOLLAND GUMMIHJULSLÆSSERE LW/W W170C FPT F4HFE613Y TIER 4I (2012-2016)



MOTOR FPT F4HFE613Y
Kapacitet: 13,2 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Agrisynth LSP Ultra 10W-40

PRODUKTANBEFALING 2

Agrisynth MSP 10W-40

PRODUKTANBEFALING 3

Agridiesel MSP 15W-40

DIFFERENTIALE BAG ZF MT-L3075-II
Kapacitet: 23 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

PRODUKTANBEFALING 2

Kroontrak MTH 10W-30

PRODUKTANBEFALING 3

Agrifluid HT

FORAKSEL ZF MT-L3085-II
Kapacitet: 35 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

PRODUKTANBEFALING 2

Kroontrak MTH 10W-30

PRODUKTANBEFALING 3

Agrifluid HT

GEAR POWERSHIFT 4/3
Kapacitet: 34 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

PRODUKTANBEFALING 2

Kroontrak MTH 10W-30

PRODUKTANBEFALING 3

Agrifluid HT

GEAR POWERSHIFT 5/3

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

PRODUKTANBEFALING 2

Kroontrak MTH 10W-30

PRODUKTANBEFALING 3

Agrifluid HT

NEW HOLLAND GUMMIHJULSLÆSSERE LW/W W170C FPT F4HFE613Y TIER 4I (2012- 2016)



HYDRAULISK SYSTEM

Kapacitet: 90,8 liter (Tank), Kapacitet: 177,8 liter (Total)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus Biosynth 46

PRODUKTANBEFALING 2

Perlus H 46

SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

MoS2 Grease EP 2

KØLESYSTEM

Kapacitet: 28,4 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.