

NEW HOLLAND GUMMIHJULSLÆSSERE LW/W W270C ZB FPT F2CFE614C TIER 4i (2012-2015)



MOTOR New Holland/FPT F2CFE614C Tier 4i
Kapacitet: 28,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP Ultra 10W-40	Agrisynth MSP 10W-40	Agridiesel MSP 15W-40

Kontroller alle 10 timer, skift alle 500 timer

DIFFERENTIALE BAG
Kapacitet: 42 liter (Alle)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT

Kontroller alle 500 timer, skift alle 1500 timer

DIFFERENTIALE FOR
Kapacitet: 62 liter (Heavy Duty), Kapacitet: 42 liter (Standard)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT

Kontroller alle 500 timer, skift alle 1500 timer

GEAR POWERSHIFT 4/3
Kapacitet: 45,4 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Multifleet SHPD 10W-40

Kontroller alle 50 timer, skift alle 1500 timer

NAVREDUKTIONER BAG

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT

Kontroller alle 500 timer, skift alle 1500 timer

NEW HOLLAND GUMMIHJULSLÆSSERE LW/W W270C ZB FPT F2CFE614C TIER 4I (2012-2015)



NAVREDUKTIONER FOR

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT

Kontroller alle 500 timer, skift alle 1500 timer

HYDRAULISK SYSTEM

Kapacitet: 134 liter (Hydrauliktank), Kapacitet: 250 liter (System)

ANVEND		KLIMA
Foretrukne		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus Biosynth 46	Perlus H 46	

Kontroller alle 50 timer, skift alle 2000 timer

ANVEND		KLIMA
Alternativ (acceptabel)		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus Biosynth 46	Perlus H 46	

Kontroller alle 50 timer, skift alle 2000 timer

KØLESYSTEM

Kapacitet: 56,8 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant SP 15+	Coolant SP 12	

Kontroller alle 50 timer, skift alle 2000 timer

SCR-SYSTEM

Kapacitet: 91 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.