

NEW HOLLAND GUMMIHJULSLÆSSERE LW/W W60 B TC CNH F5C E9454G TIER 3A (2008-2014)



MOTOR CNH F5C E9454
Kapacitet: 8,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agridiesel MSP 15W-40

PRODUKTANBEFALING 2
Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 3
Dieselfleet CD+ 15W-40

DIFFERENTIALE BAG
Kapacitet: 8 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube LS 80W-90

Skift alle 1000 timer

DIFFERENTIALE FOR
Kapacitet: 8 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube LS 80W-90

Skift alle 1000 timer

GEAR HYDROSTATISK 2/2
Kapacitet: 0,75 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube LS 80W-90

Skift alle 1000 timer

NAVREDUKTIONER BAG
Kapacitet: 0,7 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube LS 80W-90

Skift alle 1000 timer

NEW HOLLAND GUMMIHJULSLÆSSERE LW/W W60 B TC CNH F5C E9454G TIER 3A (2008-2014)

**NAVREDUKTIONER FOR**

Kapacitet: 0,6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90*Skift alle 1000 timer***HYDRAULISK SYSTEM**

Kapacitet: 67 liter (System), Kapacitet: 40 liter (Tank)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus Biosynth 46

PRODUKTANBEFALING 2

Perlus H 46*Skift alle 3000 timer***SMØREPUNKTER/NIPLER**

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Q7 MP Calcep Grease WR 2

PRODUKTANBEFALING 2

Caliplex HD Grease EP 2

PRODUKTANBEFALING 3

Q5 MP Calcep Grease EP 2**KØLESYSTEM**

Kapacitet: 16,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.