

NEW HOLLAND MINI-GRAVERE E/EC/EH E10SR YANMAR 2TNV70-WYB TIER 4 (2010-2015)



MOTOR Yanmar 2TNV70
Kapacitet: 3,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40

Skift alle 250 timer/ 3 måneder

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40

Skift alle 50 timer

HYDRAULISK SYSTEM
Kapacitet: 10 liter (Tank), Kapacitet: 15 liter (Total)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus Biosynth 46	Perlus H 46	

Skift alle 5000 timer

SMØREPUNKTER/NIPLER

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
MoS2 Grease EP 2		

KØLESYSTEM
Kapacitet: 3,7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant SP 15+	Coolant SP 12	

Skift alle 1000 timer/ 12 måneder

NEW HOLLAND MINI-GRAVERE E/EC/EH E10SR YANMAR 2TNV70-WYB TIER 4 (2010-2015)

**DREJEGEAR**

Kapacitet: 70 gram

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

MoS2 Grease EP 2*Skift alle 250 timer/ 3 måneder***KØREREDUKTIONSENHED**

Kapacitet: 0,33 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 85W-140

PRODUKTANBEFALING 2

Unigear LS GL-3/GL-5 85W-140*Skift alle 2000 timer*

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 85W-140

PRODUKTANBEFALING 2

Unigear LS GL-3/GL-5 85W-140*Skift alle 6 måneder/ 500 timer***NEDRE RULLER**

Kapacitet: 0,07 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 85W-140

PRODUKTANBEFALING 2

Unigear LS GL-3/GL-5 85W-140*Skift alle 2000 timer***RULLER**

Kapacitet: 0,03 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 85W-140

PRODUKTANBEFALING 2

Unigear LS GL-3/GL-5 85W-140*Skift alle 2000 timer*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.