

NEW HOLLAND MINI-GRAVERE E/EC/EH E16 YANMAR 3TNE74-N (2004-2005)



MOTOR Yanmar 3TNE74-N
Kapacitet: 3,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agridiesel MSP 15W-40

PRODUKTANBEFALING 2
Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 3
Dieselfleet CD+ 15W-40

Skift alle 500 timer

HYDRAULISK SYSTEM

Kapacitet: 14,5 liter (Tank), Kapacitet: 22 liter (Total)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Perlus Biosynth 46

PRODUKTANBEFALING 2
Perlus H 46

Skift alle 2000 timer

SMØREPUNKTER/NIPLER

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Q7 MP Calcep Grease WR 2

PRODUKTANBEFALING 2
Caliplex HD Grease EP 2

PRODUKTANBEFALING 3
Q5 MP Calcep Grease EP 2

KØLESYSTEM

Kapacitet: 3,7 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Coolant SP 15+

PRODUKTANBEFALING 2
Coolant SP 12

DREJEGEAR

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
MoS2 Grease EP 2

NEW HOLLAND MINI-GRAVERE E/EC/EH E16 YANMAR 3TNE74-N (2004-2005)



KØREREDUKTIONSENHED

Kapacitet: 0,33 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 85W-140

PRODUKTANBEFALING 2

Unigear LS GL-3/GL-5 85W-140

Skift alle 2000 timer

NEDRE RULLER

Kapacitet: 0,06 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Skift alle 2000 timer

RULLER

Kapacitet: 0,03 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Skift alle 2000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.