

NEW HOLLAND RENDEGRAVER B/LB/NH B110B 4WS CNH 445TA/EGH (2008-2012)



MOTOR CNH 445TA/EGH
Kapacitet: 12,8 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agridiesel MSP 15W-40

PRODUKTANBEFALING 2
Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 3
Dieselfleet CD+ 15W-40

DIFFERENTIALE BAG
Kapacitet: 11 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agrifluid HT-Plus

PRODUKTANBEFALING 2
Kroontrak MTH 10W-30

PRODUKTANBEFALING 3
Agrifluid HT

DIFFERENTIALE FOR
Kapacitet: 10,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agrifluid HT-Plus

PRODUKTANBEFALING 2
Kroontrak MTH 10W-30

PRODUKTANBEFALING 3
Agrifluid HT

GEAR POWERSHIFT
Kapacitet: 14 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Matic 2032

GEAR POWERSHUTTLE
Kapacitet: 18 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agrifluid HT-Plus

PRODUKTANBEFALING 2
Kroontrak MTH 10W-30

PRODUKTANBEFALING 3
Agrifluid HT

NEW HOLLAND RENDEGRAVER B/LB/NH B110B 4WS CNH 445TA/EGH (2008-2012)



NAVREDUKTIONER BAG

Kapacitet: 1,3 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT

NAVREDUKTIONER FOR

Kapacitet: 1,3 liter (hvert)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT

HYDRAULISK SYSTEM

Kapacitet: 118 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT

HYDRAULISK BREMSESYSTEM

Kapacitet: 1 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
LHM +		

SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
MoS2 Grease EP 2		

NEW HOLLAND RENDEGRAVER B/LB/NH B110B 4WS CNH 445TA/EGH (2008-2012)



KØLESYSTEM

Kapacitet: 24 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.