

NEW HOLLAND RENDEGRAVER B/LB/NH B110C FPT F5HFL413B TIER 4I (2012 OG EFTER)



MOTOR FPT F5HFL413B
Kapacitet: 14 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP Ultra 10W-40	Agrisynth MSP 10W-40	Agridiesel MSP 15W-40

DIFFERENTIALE BAG

Kapacitet: 15,5 liter (2WS), Kapacitet: 11 liter (4WS)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Unigear LS GL-3/GL-5 85W-140		

DIFFERENTIALE FOR

Kapacitet: 8,6 liter (2WS), Kapacitet: 10,5 liter (4WS)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Unigear LS GL-3/GL-5 85W-140		

GEAR POWERSHIFT Carraro 4/4 4/4

Kapacitet: 20,8 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Agrifluid HT-Plus		

GEAR POWERSHUTTLE Carraro 4/3 4/3

Kapacitet: 18,5 liter (2WD), Kapacitet: 20,8 liter (4WD)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Agrifluid HT-Plus		

NEW HOLLAND RENDEGRAVER B/LB/NH B110C FPT F5HFL413B TIER 4I (2012 OG EFTER)



NAVREDUKTIONER BAG

Kapacitet: 1,3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Unigear LS GL-3/GL-5 85W-140

NAVREDUKTIONER FOR

Kapacitet: 1 liter (2WS, hver), Kapacitet: 1,3 liter (4WS, hver)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Unigear LS GL-3/GL-5 85W-140

HYDRAULISK SYSTEM

Kapacitet: 75 liter (Tank), Kapacitet: 118 liter (Total)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

PRODUKTANBEFALING 2

Kroontrak MTH 10W-30

PRODUKTANBEFALING 3

Agrifluid HT

SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

MoS2 Grease EP 2

KØLESYSTEM

Kapacitet: 24 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.