

NEW HOLLAND RENDEGRAVER B/LB/NH B95C LR FPT F5HFL413B*A TIER 4I (2012 OG EFTER)



MOTOR FPT F5HFL413B
Kapacitet: 14 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Agrisynth LSP Ultra 10W-40

PRODUKTANBEFALING 2

Agrisynth MSP 10W-40

PRODUKTANBEFALING 3

Agridiesel MSP 15W-40

DIFFERENTIALE BAG

Kapacitet: 15,5 liter (2WS), Kapacitet: 11 liter (4WS)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Unigear LS GL-3/GL-5 85W-140

DIFFERENTIALE FOR

Kapacitet: 8,6 liter (2WS), Kapacitet: 10,5 liter (4WS)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Unigear LS GL-3/GL-5 85W-140

GEAR POWERSHIFT Carraro 4/4 4/4

Kapacitet: 20,8 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

GEAR POWERSHUTTLE Carraro 4/3 4/3

Kapacitet: 18,5 liter (2WD), Kapacitet: 20,8 liter (4WD)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

NEW HOLLAND RENDEGRAVER B/LB/NH B95C LR FPT F5HFL413B*A TIER 4I (2012 OG EFTER)

**NAVREDUKTIONER BAG**

Kapacitet: 1,3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Unigear LS GL-3/GL-5 85W-140**NAVREDUKTIONER FOR**

Kapacitet: 1 liter (2WS, hver), Kapacitet: 1,3 liter (4WS, hver)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Unigear LS GL-3/GL-5 85W-140**HYDRAULISK SYSTEM**

Kapacitet: 75 liter (Tank), Kapacitet: 118 liter (Total)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

PRODUKTANBEFALING 2

Kroontrak MTH 10W-30

PRODUKTANBEFALING 3

Agrifluid HT**SMØREPUNKTER/NIPLER**

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

MoS2 Grease EP 2**KØLESYSTEM**

Kapacitet: 24 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.