

NEW HOLLAND RENDEGRAVER B/LB/NH LB75.B CNH 445T/M2 (2000-2006)



MOTOR CNH 445T/M2

Kapacitet: 13,6 liter (2WS), Kapacitet: 12,8 liter (4WS)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40

Skift alle 300 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1		
Kroontrak MTH 10W-30		

Skift alle 50 timer

DIFFERENTIALE BAG

Kapacitet: 5,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT

Skift alle 1200 timer/ 12 måneder

DIFFERENTIALE FOR

Kapacitet: 5,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT

Skift alle 1200 timer/ 12 måneder

GEAR POWERSHIFT 4/4

Kapacitet: 18 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Matic 2032		

Skift alle 600 timer

NEW HOLLAND RENDEGRAVER B/LB/NH LB75.B CNH 445T/M2 (2000-2006)



GEAR POWERSHUTTLE

Kapacitet: 18 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

PRODUKTANBEFALING 2

Kroontrak MTH 10W-30

PRODUKTANBEFALING 3

Agrifluid HT

Skift alle 600 timer

NAVREDUKTIONER

Kapacitet: 1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

PRODUKTANBEFALING 2

Kroontrak MTH 10W-30

PRODUKTANBEFALING 3

Agrifluid HT

Skift alle 1200 timer/ 12 måneder

HYDRAULISK SYSTEM

Kapacitet: 137 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

PRODUKTANBEFALING 2

Kroontrak MTH 10W-30

PRODUKTANBEFALING 3

Agrifluid HT

Skift alle 1200 timer/ 12 måneder

HYDRAULISK BREMSESYSTEM

Kapacitet: 1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

LHM +

SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

MoS2 Grease EP 2

NEW HOLLAND RENDEGRAVER B/LB/NH LB75.B CNH 445T/M2 (2000-2006)



KØLESYSTEM

Kapacitet: 24 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.