

# NISSAN GAFFELTRUCK, DIESEL DX-15 QD32 (2007 OG EFTER)



## MOTOR Nissan QD32

|        |                  |
|--------|------------------|
| ANVEND | KLIMA            |
| Normal | Middelhavsagtigt |

|                               |                               |                          |
|-------------------------------|-------------------------------|--------------------------|
| PRODUKTANBEFALING 1           | PRODUKTANBEFALING 2           | PRODUKTANBEFALING 3      |
| <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> | <b>Multifleet SCD 30</b> |

Kontroller alle 10 timer, skift alle 500 timer

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

|                             |                             |                               |
|-----------------------------|-----------------------------|-------------------------------|
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2         | PRODUKTANBEFALING 3           |
| <b>Kroontrak MTH 10W-30</b> | <b>Synfleet SHPD 10W-40</b> | <b>Multifleet SHPD 10W-40</b> |

Kontroller alle 10 timer, skift alle 500 timer

## DIFFERENTIALE FOR

|        |                  |
|--------|------------------|
| ANVEND | KLIMA            |
| Normal | Middelhavsagtigt |

|                              |  |  |
|------------------------------|--|--|
| PRODUKTANBEFALING 1          |  |  |
| <b>Gearlube GL-5 85W-140</b> |  |  |

Skift alle 12 måneder/ 2400 timer

|        |       |
|--------|-------|
| ANVEND | KLIMA |
| Normal | Koldt |

|                             |                                    |  |
|-----------------------------|------------------------------------|--|
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |  |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

Skift alle 12 måneder/ 2400 timer

## GEAR AUTOMATISK

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

|                        |                     |  |
|------------------------|---------------------|--|
| PRODUKTANBEFALING 1    | PRODUKTANBEFALING 2 |  |
| <b>ATF Dexron II-D</b> | <b>ATF-F (Ford)</b> |  |

Skift alle 6 måneder/ 1200 timer

## HYDRAULISK SYSTEM

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

|                     |  |  |
|---------------------|--|--|
| PRODUKTANBEFALING 1 |  |  |
| <b>Perlus H 32</b>  |  |  |

Skift alle 12 måneder/ 2400 timer

# NISSAN GAFFELTRUCK, DIESEL DX-15 QD32 (2007 OG EFTER)



## HYDRAULISK BREMSESYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Drauliquid DOT 3***Skift alle 12 måneder/ 2400 timer*

## SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Gear Grease EP 1***Skift alle 3 måneder/ 600 timer*

## SMØREPUNKTER/NIPLER HJULLEJER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Labora Grease**

PRODUKTANBEFALING 2

**Q5 MP Calcep Grease EP 2**

PRODUKTANBEFALING 3

**MP Lithep Grease EP 2***Skift alle 12 måneder/ 2400 timer*

## KØLESYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Coolant -38 Organic NF**

PRODUKTANBEFALING 2

**Coolant -26**

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.