

NISSAN GAFFELTRUCK, DIESEL F04D50Q



MOTOR

Kapacitet: 12 liter

ANVEND	KLIMA
Normal	Tropisk

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Multifleet SCD 50	Multifleet SCD 40	

Skift alle 1 måneder/ 200 timer

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1		
Multifleet SCD 30		

Skift alle 1 måneder/ 200 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40

Skift alle 1 måneder/ 200 timer

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1		
Multifleet SCD 10W		

Skift alle 1 måneder/ 200 timer

DIFFERENTIALE

Kapacitet: 9,1 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Skift alle 1 måneder/ 200 timer

GEAR + MOMENTOMFORMER Powershift

Kapacitet: 15 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
ATF Almirol		

Skift alle 6 måneder/ 1200 timer



HYDRAULISK SYSTEM

Kapacitet: 64,4 liter (Hydrauliktank)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 32

Skift alle 12 måneder/ 2400 timer

HYDRAULISK BREMSESYSTEM

Kapacitet: 0,15 liter (Tank)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 3

FEDTSMURTE STEDER/NIPLER CHASSIS

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gear Grease EP 1

SMØREPUNKTER/NIPLER HJULLEJER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

KØLESYSTEM

Kapacitet: 14,7 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.