

# PEL-JOB GRAVEMASKINER MED LARVEBÅND EB706



| MOTOR Mitsubishi S4S                                  |                               |         |
|-------------------------------------------------------|-------------------------------|---------|
| ANVEND                                                |                               | KLIMA   |
| Normal                                                |                               | Moderat |
| PRODUKTANBEFALING 1                                   | PRODUKTANBEFALING 2           |         |
| <b>Dieselfleet CD+ 15W-40</b>                         | <b>Multifleet SHPD 15W-40</b> |         |
| <i>Kontroller alle 10 timer, skift alle 250 timer</i> |                               |         |

| HYDRAULISK SYSTEM            |  |                  |
|------------------------------|--|------------------|
| ANVEND                       |  | KLIMA            |
| Normal                       |  | Middelhavsagtigt |
| PRODUKTANBEFALING 1          |  |                  |
| <b>Perlus H 68</b>           |  |                  |
| <i>Skift alle 1000 timer</i> |  |                  |

| ANVEND                       |  | KLIMA   |
|------------------------------|--|---------|
| Normal                       |  | Moderat |
| PRODUKTANBEFALING 1          |  |         |
| <b>Perlus H 46</b>           |  |         |
| <i>Skift alle 1000 timer</i> |  |         |

| ANVEND                       |  | KLIMA   |
|------------------------------|--|---------|
| Normal                       |  | Arktisk |
| PRODUKTANBEFALING 1          |  |         |
| <b>Perlus H 32</b>           |  |         |
| <i>Skift alle 1000 timer</i> |  |         |

| SMØREPUNKTER/NIPLER  |                                 |                              |
|----------------------|---------------------------------|------------------------------|
| ANVEND               |                                 | KLIMA                        |
| Normal               |                                 | Moderat                      |
| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
| <b>Labora Grease</b> | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

| KØREREDUKTIONSENHED          |                                    |         |
|------------------------------|------------------------------------|---------|
| ANVEND                       |                                    | KLIMA   |
| Normal                       |                                    | Moderat |
| PRODUKTANBEFALING 1          | PRODUKTANBEFALING 2                |         |
| <b>Gearlube GL-5 80W-90</b>  | <b>Unigear HS GL-3/GL-5 80W-90</b> |         |
| <i>Skift alle 1000 timer</i> |                                    |         |

# PEL-JOB GRAVEMASKINER MED LARVEBÅND EB706



## LARVEBÅNDSRULLER

| ANVEND                      |                                    | KLIMA   |
|-----------------------------|------------------------------------|---------|
| Normal                      |                                    | Moderat |
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |         |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |         |

## SPOR MELLEMHJUL

| ANVEND                      |                                    | KLIMA   |
|-----------------------------|------------------------------------|---------|
| Normal                      |                                    | Moderat |
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |         |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |         |

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*