

PISTENBULLY PISTENBULLY PB 400 W



MOTOR Cummins QSL9
Kapacitet: 21 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agrisynth LSP 10W-40

PRODUKTANBEFALING 2
Armado Synth 10W-40

Kontroller alle 10 timer, skift alle 500 timer/ 12 måneder

GEAR/HYDRAULISK SYSTEM
Kapacitet: 80 liter (System)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
ATF Dexron II-D

Skift alle 1200 timer/ 12 måneder

GEARKASSEKABEL
Kapacitet: 10 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube Racing 75W-140

PRODUKTANBEFALING 2
Abacot MEP Synth 220

PRODUKTANBEFALING 3
Abacot MEP 220

Skift alle 800 timer/ 12 måneder

REDUKTIONSGEARKASSE
Kapacitet: 1,8 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Gear 1011

PRODUKTANBEFALING 2
Syngear TDL 75W-90

PRODUKTANBEFALING 3
Abacot MEP Synth 220

Skift alle 800 timer/ 12 måneder

SLUT-REDUKTION
Kapacitet: 4 liter (hver side)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Gear 1011

PRODUKTANBEFALING 2
Syngear TDL 75W-90

PRODUKTANBEFALING 3
Abacot MEP Synth 220

Skift alle 800 timer/ 12 måneder

PISTENBULLY PISTENBULLY PB 400 W



SPILBREMSE

Kapacitet: 0,08 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Armado Synth 10W-40

SVINGGEARKASSE

Kapacitet: 0,9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

PRODUKTANBEFALING 3

Abacot MEP Synth 220

Skift alle 600 timer/ 12 måneder

SMØREPUNKTER/NIPLER GENERELT

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 2

MP Lithep Grease EP 2

KØLESYSTEM

Kapacitet: 30 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

Skift alle 2000 timer/ 24 måneder

SPIL

Kapacitet: 0,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

PRODUKTANBEFALING 3

Abacot MEP Synth 220

Skift alle 600 timer/ 12 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.