

PUMA GAFFELTRUCK, DIESEL FD-30 - II/III



MOTOR Isuzu		
ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Dieselfleet CD+ 15W-40	PRODUKTANBEFALING 2 Multifleet SHPD 10W-40	PRODUKTANBEFALING 3 Multifleet SHPD 15W-40
Skift alle 1 måneder/ 200 timer		

MOTOR Nissan		
ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Dieselfleet CD+ 15W-40	PRODUKTANBEFALING 2 Multifleet SHPD 15W-40	
Skift alle 1 måneder/ 200 timer		

MOTOR Perkins 1004.4		
ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Dieselfleet CD+ 15W-40	PRODUKTANBEFALING 2 Multifleet SHPD 15W-40	
Skift alle 1 måneder/ 200 timer		

DIFFERENTIALE		
ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Gearlube GL-5 80W-90	PRODUKTANBEFALING 2 Unigear HS GL-3/GL-5 80W-90	
Skift alle 1000 timer/ 6 måneder		

GEAR Powershift		
ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 ATF Dexron II-D		
Skift alle 1000 timer/ 6 måneder		



GEAR MANUEL

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Skift alle 1000 timer/ 6 måneder

STYREKSEL

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

HYDRAULIKSYSTEM SERVOSTYRING

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Perlus H 46		

Skift alle 1000 timer/ 6 måneder

SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.