

# SCHÄFFER GUMMIHJULSLÆSSERE 222

## KUBOTA D1005



**MOTOR** Kubota D1005  
Kapacitet: 4,2 liter

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

|                             |                             |                             |
|-----------------------------|-----------------------------|-----------------------------|
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2         | PRODUKTANBEFALING 3         |
| <b>Kroontrak CVT 10W-40</b> | <b>Kroontrak MTH 10W-30</b> | <b>Synfleet SHPD 10W-40</b> |

Skift alle 400 timer

|                |         |
|----------------|---------|
| ANVEND         | KLIMA   |
| Første Service | Moderat |

|                             |                             |                             |
|-----------------------------|-----------------------------|-----------------------------|
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2         | PRODUKTANBEFALING 3         |
| <b>Kroontrak CVT 10W-40</b> | <b>Kroontrak MTH 10W-30</b> | <b>Synfleet SHPD 10W-40</b> |

Skift alle 50 timer

**DIFFERENTIALE BAG**  
Kapacitet: 2,5 liter

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

|                             |                                    |  |
|-----------------------------|------------------------------------|--|
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |  |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

Kontroller alle 200 timer, skift alle 800 timer

|                |         |
|----------------|---------|
| ANVEND         | KLIMA   |
| Første Service | Moderat |

|                             |                                    |  |
|-----------------------------|------------------------------------|--|
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |  |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

Skift alle 200 timer

**DIFFERENTIALE FOR**  
Kapacitet: 2,5 liter

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

|                             |                                    |  |
|-----------------------------|------------------------------------|--|
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |  |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

Kontroller alle 200 timer, skift alle 800 timer

|                |         |
|----------------|---------|
| ANVEND         | KLIMA   |
| Første Service | Moderat |

|                             |                                    |  |
|-----------------------------|------------------------------------|--|
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |  |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

Skift alle 200 timer

# SCHÄFFER GUMMIHJULSLÆSSERE 222

## KUBOTA D1005



### HYDRAULISK SYSTEM

Kapacitet: 40 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2 |  |
|---------------------|---------------------|--|
| <b>Perlus H 46</b>  | <b>Perlus AF 46</b> |  |

Kontroller alle 8 timer, skift alle 800 timer

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Moderat |

| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2 |  |
|---------------------|---------------------|--|
| <b>Perlus H 46</b>  | <b>Perlus AF 46</b> |  |

Skift alle 200 timer

### SMØREPUNKTER/NIPLER

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
|----------------------|---------------------------------|------------------------------|
| <b>Labora Grease</b> | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

Kontroller alle 8 timer

### KØLESYSTEM

Kapacitet: 3,1 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1           | PRODUKTANBEFALING 2 |  |
|-------------------------------|---------------------|--|
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>  |  |

Kontroller alle 8 timer, skift alle 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.