

SCHÄFFER GUMMIHJULSLÆSSERE 450T DEUTZ



MOTOR Deutz

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Dieselfleet MSP 15W-40

Skift alle 400 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Dieselfleet MSP 15W-40

Skift alle 50 timer

DIFFERENTIALE FOR Kapacitet: 4,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

Kontroller alle 200 timer, skift alle 800 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

Skift alle 200 timer

TRANSAKSEL BAG- Kapacitet: 5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

Kontroller alle 200 timer, skift alle 800 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

Skift alle 200 timer

SCHÄFFER GUMMIHJULSLÆSSERE 450T DEUTZ



HYDRAULISK BREMSESYSTEM DOT-SYSTEM

ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Drauliquid-LV Super DOT 4	PRODUKTANBEFALING 2 Drauliquid-S DOT 4	PRODUKTANBEFALING 3 Drauliquid DOT 3

Kontroller alle 8 timer, skift alle 24 måneder

HYDRAULISK BREMSESYSTEM MINERALOLIESYSTEM

ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 ATF Dexron II-D		

Kontroller alle 8 timer, skift alle 24 måneder

HYDRAULISK SYSTEM

Kapacitet: 60 liter

ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Perlus H 46	PRODUKTANBEFALING 2 Perlus AF 46	

Kontroller alle 8 timer, skift alle 800 timer

ANVEND Første Service		KLIMA Moderat
PRODUKTANBEFALING 1 Perlus H 46	PRODUKTANBEFALING 2 Perlus AF 46	

Skift alle 200 timer

SMØREPUNKTER/NIPLER

ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Labora Grease	PRODUKTANBEFALING 2 Q5 MP Calcep Grease EP 2	PRODUKTANBEFALING 3 MP Lithep Grease EP 2

Kontroller alle 8 timer

SCHÄFFER GUMMIHJULSLÆSSERE 450T DEUTZ



KØLESYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Kontroller alle 8 timer, skift alle 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.