

SHANTUI BULLDOZERE SD16 WEICHA WD615T1-3A



MOTOR Weichai WD615T1-3A
Kapacitet: 26 liter (Servicepåfyldning), Kapacitet: 45 liter (Tør efterfyld)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40

Kontroller alle 10 timer, skift alle 500 timer

GEAR 3/3
Kapacitet: 47 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40

Kontroller alle 10 timer, skift alle 1000 timer

MOMENTOMFORMER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40

Kontroller alle 10 timer, skift alle 1000 timer

SLUTDREV
Kapacitet: 23 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40

Kontroller alle 250 timer, skift alle 1000 timer

HYDRAULISK SYSTEM
Kapacitet: 108 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Multifleet SHPD 10W-40

Kontroller alle 250 timer, skift alle 1000 timer

SHANTUI BULLDOZERE SD16 WEICHA WD615T1-3A



SMØREPUNKTER/NIPLER		
ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Labora Grease	PRODUKTANBEFALING 2 Q5 MP Calcep Grease EP 2	PRODUKTANBEFALING 3 MP Lithep Grease EP 2

KØLESYSTEM Kapacitet: 79 liter		
ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Coolant -38 Organic NF	PRODUKTANBEFALING 2 Coolant -26	

SPÆNDINGSHJUL Kapacitet: 0,25 liter		
ANVEND Normal		KLIMA Middelhavsagtigt
PRODUKTANBEFALING 1 Unigear LS GL-3/GL-5 85W-140		

STYRINGSHJUL Kapacitet: 0,25 liter		
ANVEND Normal		KLIMA Middelhavsagtigt
PRODUKTANBEFALING 1 Unigear LS GL-3/GL-5 85W-140		

STØTTEVALSER Kapacitet: 0,25 liter		
ANVEND Normal		KLIMA Middelhavsagtigt
PRODUKTANBEFALING 1 Unigear LS GL-3/GL-5 85W-140		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.