

SMV GAFFELTRUCK SL 13,6-600 AV



MOTOR Scania DI 9
Kapacitet: 20-25 liter

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Multifleet SCD 50	Multifleet SCD 40	Multifleet SCD 30

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40

DIFFERENTIALE
Kapacitet: 20 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Gearlube HS GL-5 80W-140		

GEARKASSE
Kapacitet: 27 liter

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Multifleet SCD 30	Gear Oil Alcat 30	

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Multifleet SCD 10W	Gear Oil Alcat 10W	SP Matic 2032

NAVREDUKTIONER
Kapacitet: 7 liter (hvert)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Gearlube HS GL-5 80W-140		

**HYDRAULISK SYSTEM**

Kapacitet: 105 liter (akselafstand: 3.000 mm), Kapacitet: 142 liter (akselafstand: 3.250 mm), Kapacitet: 175 liter (akselafstand: 3.500 mm), Kapacitet: 208 liter (akselafstand: 3.750 mm)

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2**KØLESYSTEM**

Kapacitet: 50 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.