

# SMV GAFFELTRUCK SL 52-1200 A (1995-2001)



**MOTOR** Scania  
Kapacitet: 22-30 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1  
**Agridiesel MSP 15W-40**

PRODUKTANBEFALING 2  
**Agridiesel CRD+ 15W-40**

PRODUKTANBEFALING 3  
**Kroontrak MTH 10W-30**

*Skift alle 250 timer*

**DIFFERENTIALE**  
Kapacitet: 38 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1  
**Gearlube HS GL-5 80W-140**

*Kontroller alle 250 timer, skift alle 2000 timer*

**GEARKASSE**  
Kapacitet: 42 liter

ANVEND  
Normal

KLIMA  
Middelhavsagtigt

PRODUKTANBEFALING 1  
**Gear Oil Alcat 30**

*Skift alle 1000 timer*

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1  
**Gear Oil Alcat 10W**

PRODUKTANBEFALING 2  
**ATF Dexron II-D**

*Skift alle 1000 timer*

**NAVREDUKTIONER**  
Kapacitet: 11,5 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1  
**Gearlube HS GL-5 80W-140**

*Kontroller alle 250 timer, skift alle 2000 timer*

**HYDRAULISK SYSTEM**  
Kapacitet: 465 liter (Hydrauliktank)

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

# SMV GAFFELTRUCK SL 52-1200 A (1995-2001)



## SMØREPUNKTER/NIPLER

| ANVEND               |                                 | KLIMA                        |
|----------------------|---------------------------------|------------------------------|
| Normal               |                                 | Moderat                      |
| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
| <b>Labora Grease</b> | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

## KØLESYSTEM

Kapacitet: 60 liter

| ANVEND                        |                     | KLIMA   |
|-------------------------------|---------------------|---------|
| Normal                        |                     | Moderat |
| PRODUKTANBEFALING 1           | PRODUKTANBEFALING 2 |         |
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>  |         |

*Kontroller alle 1000 timer*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*