

# SVETRUCK GAFFELTRUCKER 1875-33 VOLVO TAD6



## MOTOR Volvo TAD6

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

|                               |                           |                                     |
|-------------------------------|---------------------------|-------------------------------------|
| PRODUKTANBEFALING 1           | PRODUKTANBEFALING 2       | PRODUKTANBEFALING 3                 |
| <b>Agridiesel CRD+ 15W-40</b> | <b>Armado Synth 5W-30</b> | <b>Dieselfleet LSP Ultra 10W-30</b> |

Kontroller alle 10 timer, skift alle 2 måneder/ 400 timer

|                |         |
|----------------|---------|
| ANVEND         | KLIMA   |
| Første Service | Moderat |

|                               |                           |                                     |
|-------------------------------|---------------------------|-------------------------------------|
| PRODUKTANBEFALING 1           | PRODUKTANBEFALING 2       | PRODUKTANBEFALING 3                 |
| <b>Agridiesel CRD+ 15W-40</b> | <b>Armado Synth 5W-30</b> | <b>Dieselfleet LSP Ultra 10W-30</b> |

Skift alle 50 timer

## DIFFERENTIALE FOR

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Tropisk |

|                                 |  |  |
|---------------------------------|--|--|
| PRODUKTANBEFALING 1             |  |  |
| <b>Gearlube HS GL-5 80W-140</b> |  |  |

Skift alle 5 måneder/ 1000 timer

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

|                             |                                    |  |
|-----------------------------|------------------------------------|--|
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |  |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

Skift alle 5 måneder/ 1000 timer

## GEAR ZF ErgoPower 4/3

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

|                                  |                          |                     |
|----------------------------------|--------------------------|---------------------|
| PRODUKTANBEFALING 1              | PRODUKTANBEFALING 2      | PRODUKTANBEFALING 3 |
| <b>Agrifluid Synth XHP Ultra</b> | <b>Agrifluid HT-Plus</b> | <b>Agrifluid HT</b> |

Kontroller alle 10 timer, skift alle 5 måneder/ 1000 timer

## HYDRAULISK SYSTEM

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

|                           |                     |  |
|---------------------------|---------------------|--|
| PRODUKTANBEFALING 1       | PRODUKTANBEFALING 2 |  |
| <b>Perlus Biosynth 46</b> | <b>Perlus H 46</b>  |  |

Kontroller alle 10 timer, skift alle 10 måneder/ 2000 timer

# SVETRUCK GAFFELTRUCKER 1875-33 VOLVO TAD6



## SMØREPUNKTER/NIPLER

| ANVEND               |                                 | KLIMA                        |
|----------------------|---------------------------------|------------------------------|
| Normal               |                                 | Moderat                      |
| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
| <b>Labora Grease</b> | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

## KØLESYSTEM HYDRAULISKE BREMSER MED SEPARAT TANK

| ANVEND                   |  | KLIMA   |
|--------------------------|--|---------|
| Normal                   |  | Moderat |
| PRODUKTANBEFALING 1      |  |         |
| <b>Agrifluid HT-Plus</b> |  |         |

*Kontroller alle 10 timer*

## KØLESYSTEM HYDRAULISKE BREMSER UDEN SEPARAT TANK

| ANVEND                    |                     | KLIMA   |
|---------------------------|---------------------|---------|
| Normal                    |                     | Moderat |
| PRODUKTANBEFALING 1       | PRODUKTANBEFALING 2 |         |
| <b>Perlus Biosynth 46</b> | <b>Perlus H 46</b>  |         |

*Kontroller alle 10 timer*

## KØLESYSTEM MOTOR

| ANVEND                |                      | KLIMA   |
|-----------------------|----------------------|---------|
| Normal                |                      | Moderat |
| PRODUKTANBEFALING 1   | PRODUKTANBEFALING 2  |         |
| <b>Coolant SP 15+</b> | <b>Coolant SP 12</b> |         |

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*