

# TADANO FAUN KRANER TIL UJÆVNT TERRÆN TR-200EXC-3 MITSUBISHI 6D16-T



## MOTOR Mitsubishi 6D16-T

Kapacitet: 20 liter, Filterkapacitet: 4 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Tropisk |

PRODUKTANBEFALING 1

**Multifleet SCD 40**

| ANVEND | KLIMA            |
|--------|------------------|
| Normal | Middelhavsagtigt |

PRODUKTANBEFALING 1

**Multifleet SCD 30**

| ANVEND | KLIMA |
|--------|-------|
| Normal | Koldt |

PRODUKTANBEFALING 1

**Multifleet SCD 20W-20**

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Arktisk |

PRODUKTANBEFALING 1

**Multifleet SCD 10W**

## DIFFERENTIALE

Kapacitet: 14 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

PRODUKTANBEFALING 1

**Gearlube GL-5 80W-90**

PRODUKTANBEFALING 2

**Unigear HS GL-3/GL-5 80W-90**

*Skift alle 2000 timer/ 24 måneder*

## MOMENTOMFORMER 4/1

Kapacitet: 25 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

PRODUKTANBEFALING 1

**ATF Dexron II-D**

*Skift alle 1000 timer/ 12 måneder*

# TADANO FAUN KRANER TIL UJÆVNT TERRÆN TR-200EXC-3 MITSUBISHI 6D16-T



## NAVREDUKTIONER

Kapacitet: 2,5 liter

| ANVEND                      |                                    | KLIMA   |
|-----------------------------|------------------------------------|---------|
| Normal                      |                                    | Moderat |
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |         |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |         |

Skift alle 2000 timer/ 24 måneder

## HYDRAULISK SYSTEM

Kapacitet: 300 liter (Tank), Kapacitet: 410 liter (Total)

| ANVEND              |                     | KLIMA            |
|---------------------|---------------------|------------------|
| Normal              |                     | Middelhavsagtigt |
| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2 |                  |
| <b>Perlus H 46</b>  | <b>Perlus H 68</b>  |                  |

Skift alle 2000 timer/ 24 måneder

| ANVEND              |  | KLIMA   |
|---------------------|--|---------|
| Normal              |  | Moderat |
| PRODUKTANBEFALING 1 |  |         |
| <b>Perlus H 32</b>  |  |         |

Skift alle 2000 timer/ 24 måneder

| ANVEND              |                     | KLIMA            |
|---------------------|---------------------|------------------|
| Første Service      |                     | Middelhavsagtigt |
| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2 |                  |
| <b>Perlus H 46</b>  | <b>Perlus H 68</b>  |                  |

Skift alle 250 timer

| ANVEND              |  | KLIMA   |
|---------------------|--|---------|
| Første Service      |  | Moderat |
| PRODUKTANBEFALING 1 |  |         |
| <b>Perlus H 32</b>  |  |         |

Skift alle 250 timer

## SMØREPUNKTER/NIPLER

| ANVEND               |                                 | KLIMA                        |
|----------------------|---------------------------------|------------------------------|
| Normal               |                                 | Moderat                      |
| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
| <b>Labora Grease</b> | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

# TADANO FAUN KRANER TIL UJÆVNT TERRÆN TR-200EXC-3 MITSUBISHI 6D16-T



## HASTIGHEDSBEGRÆNSER SPIL

Kapacitet: 3,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Abacot MEP 320**

*Skift alle 1000 timer/ 12 måneder*

## STÅLWIRER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Compound OGL**

## SVINGBREMSEENHED

Kapacitet: 1,6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Abacot MEP 320**

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*