

TAKEUCHI GRAVEMASKINER MED LARVEBÅND TB TB016 S/N 116110802 -> (2012 OG EFTER)



MOTOR Yanmar 3TNV70
Kapacitet: 1,5-2,8 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Kroontrak MTH 10W-30

PRODUKTANBEFALING 2
Synfleet SHPD 10W-40

PRODUKTANBEFALING 3
Dieselfleet CD+ 15W-40

Skift alle 250 timer

ANVEND
Første Service

KLIMA
Moderat

PRODUKTANBEFALING 1
Kroontrak MTH 10W-30

PRODUKTANBEFALING 2
Synfleet SHPD 10W-40

PRODUKTANBEFALING 3
Dieselfleet CD+ 15W-40

Skift alle 50 timer

HYDRAULISK SYSTEM

Kapacitet: 23 liter (Tank), Kapacitet: 33,5 liter (Total)

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1
Perlus H 46

PRODUKTANBEFALING 2
Perlus H 68

Skift alle 2000 timer

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Perlus H 32

Skift alle 2000 timer

ANVEND
Biologisk nedbrydelig olie

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1
Perlus Biosynth 46

Skift alle 2000 timer

ANVEND
Biologisk nedbrydelig olie

KLIMA
Moderat

PRODUKTANBEFALING 1
Perlus Biosynth 32

Skift alle 2000 timer

TAKEUCHI GRAVEMASKINER MED LARVEBÅND TB TB016 S/N 116110802 -> (2012 OG EFTER)



ANVEND		KLIMA
Brug af afbryder		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 46	Perlus H 68	

Skift alle 600 timer

ANVEND		KLIMA
Brug af afbryder		Moderat
PRODUKTANBEFALING 1		
Perlus H 32		

Skift alle 600 timer

KØLESYSTEM		
Kapacitet: 3,4 liter		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

Skift alle 1000 timer

ARBEJDSUDSTYR		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Skift alle 10 timer

DREJELEJE		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Skift alle 50 timer

TAKEUCHI GRAVEMASKINER MED LARVEBÅND TB TB016 S/N 116110802 -> (2012 OG EFTER)



DREJEMOTOR TANDSTANGSDREV

ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Labora Grease	PRODUKTANBEFALING 2 Q5 MP Calcep Grease EP 2	PRODUKTANBEFALING 3 MP Lithep Grease EP 2

Skift alle 50 timer

KØREREDUKTIONSGEARKASSE

Kapacitet: 0,33 liter

ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Gearlube GL-4 80W-90	PRODUKTANBEFALING 2 Unigear HS GL-3/GL-5 80W-90	

Skift alle 1000 timer

ANVEND Første Service		KLIMA Moderat
PRODUKTANBEFALING 1 Gearlube GL-4 80W-90	PRODUKTANBEFALING 2 Unigear HS GL-3/GL-5 80W-90	

Skift alle 250 timer

LØFTEARME

ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Labora Grease	PRODUKTANBEFALING 2 Q5 MP Calcep Grease EP 2	PRODUKTANBEFALING 3 MP Lithep Grease EP 2

Skift alle 50 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.