

TAKEUCHI LÆSSEMASKINER MED LARVEBÅND TL TL250 225000665> (2008 OG EFTER)



MOTOR Kubota V3800-DI-T-E3B
Kapacitet: 13,2 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Kroontrak MTH 10W-30		

Kontroller alle 8 timer, skift alle 250 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1		
Kroontrak MTH 10W-30		

Skift alle 50 timer

HYDRAULISK SYSTEM

Kapacitet: 60 liter (Hydrauliktank), Kapacitet: 95 liter (System)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Multifleet SHPD 10W-40

Kontroller alle 8 timer, skift alle 1000 timer

SMØREPUNKTER/NIPLER

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Kontroller alle 8 timer

KØLESYSTEM

Kapacitet: 16,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

Kontroller alle 8 timer, skift alle 1000 timer

TAKEUCHI LÆSSEMASKINER MED LARVEBÅND TL TL250 225000665> (2008 OG EFTER)

**KØREREDUKTIONSGEAR**

Kapacitet: 1,6 liter (hvert)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90*Skift alle 500 timer*

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90*Skift alle 250 timer*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.